



Technical Information

AUTOSOL® Mould Protection

Product information

- Complete protection against humidity and corrosion
- Wax like, temporary preservation for all metal surfaces
- Protects moulds, industrial tools, gardening tools, cavity areas within the vehicle, etc.
- Ideally suited for objects, which are to be stored or transported
- The mould remains in top condition
- Easy to remove with AUTOSOL® Mould Cleaner
- Colourless and silicone-free.

Application

Shake well before use and hold approximately 20-30cm away from the surface. Spray evenly over required area and allow protective coating 15min to dry. In extreme conditions reapply a second coating for a thicker film and greater protection. For best results first clean the surface with AUTOSOL® Mould Cleaner.

Technical Data

Form:	aerosol
Colour:	opaque
Odour:	characteristic
Drying time:	approx. 15 min

Health and Safety

Safety Data Sheet is available separately.

Additional Information

Art.-No.: 01 014100

aerosol can 500 ml

PU: 12

The information provided in this Technical Information is based on the current status of knowledge and experience and is intended to describe the products with respect to possible applications and safety requirements. This information does not represent a legally binding assurance of specific characteristics. A legally binding assurance of specific characteristics or suitability for the concrete purpose of use can not be derived from our information. Possible trademarks and existing legislation and stipulations are to be observed by the recipient of our products under his/her own responsibility.