



## Technical Information

# AUTOSOL® Premium Foam Polish(T)

### Product information

Intensive care and shine for lacquer, plastic and rubber surfaces. The water film is broken down and the surface is given an intensive shine. The vehicle drying process is actively supported.

Does not contain NTA complexing agents or phosphate.

Contains no mineral oil hydrocarbons.

### Application

Apply pure via dosing pump.

Used for automatic car washes, self-service car washes and truck/bus car washes.

Recommended application concentration: 0.15-0.3% (15-30 ml per car)

Reaction time: max. 5 min

### Note

Do not use on hot surfaces or wheels. Do not use in direct sunlight.

If the system comes to a standstill, rinse the cleaning solution thoroughly off the vehicle with a water hose and do not allow it to dry.

### Technical Data

Form: liquid  
Colour: purple  
Odour: characteristic

### VDA Konformität

This product is VDA compliant for Class A at a maximum concentration of 0,5%.

### Health and Safety

Safety Data Sheet is available separately.

### Additional Information

Art.-Nr.: 19 66905

canister 25L

VPE: 1

The information provided in this Technical Information is based on the current status of knowledge and experience and is intended to describe the products with respect to possible applications and safety requirements. This information does not represent a legally binding assurance of specific characteristics. A legally binding assurance of specific characteristics or suitability for the concrete purpose of use cannot be derived from our information. Possible trademarks and existing legislation and stipulations are to be observed by the recipient of our products under his/her own responsibility.